

Cyclone Industriel Standard - Données Géométriques

Type	1D_2D	1.5D_2.5D	1D_3D	1.4D_2.5D	1.75_2D	1.8D_2.7D	1.5D_2.5D	1.7_2D
Source		Stairmand (1951)	Lapple (1951)	Swift (1969)	Swift (1969)	Svarovski (1992)	Stairmand (1951)	Swift (1969)
Usage	Usage général	Haut Rendement	Usage général	Haut Rendement	Usage général	Usage général	Haut Débit	Haut Débit
D	1	1	1	1	1	1	1	1
a/D	0.5	0.5	0.5	0.44	0.5	0.6	0.75	0.8
b/D	0.25	0.2	0.25	0.21	0.25	0.3	0.375	0.35
De/D	0.625	0.5	0.5	0.4	0.5	0.5	0.75	0.75
S/D	1.125	0.5	0.625	0.5	0.6	0.8	0.875	0.85
h/D	1	1.5	1	1.4	1.75	1.8	1.5	1.7
H/D	3	4	4	3.9	3.75	4.5	4	3.7
B/D	0.5	0.375	0.25	0.4	0.4	0.3	0.375	0.4
H _B /D mini	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
D _B /D mini	1	1	1	1	1	1	1	1

